

TECHNICAL SHEET

G-TEK® POLYKOR® X7 ™ POLYKOR® X7 ™ SEAMLESS KNIT -**CRINCKLE LATEX COATING - GAUGE** 18



- PolyKor ™ X7 ™ is lightweight, provides dexterity and tactile sensitivity, as well as excellent cut resistance
- The crinckle latex coating on the palm and fingertips provides a excellent dexterity on dry and slighlty wet surfaces
- · Breathable and flexible coating
- The knit wrist helps prevent dirt and debris from entering the glove

APPLICATIONS

- Glass cutting
- Metal handling
- Fastening
- Construction

CARE INSTRUCTIONS

Recommend washing gloves in slightly warm water not exceeding 40°C. A mild non-ionic detergent should be used. A 5-10 minute cycle time should be employed. Tumble dry on low - maximum temperature 140°F (60°C).

TECHNICAL DATA

| MATERIAL | PolyKor™Blend / Crinckle Latex | | | | | | |
|--------------|---|---------|---------|---------|-------|---------|--|
| CONSTRUCTION | Seamless knit | | | | | | |
| COLOR | Shell: ■ Blue / Coating: ■ Black | | | | | | |
| WRIST STYLE | Knit wrist | | | | | | |
| SIZES | 6 - 11 | | | | | | |
| PACKAGING | 1 pair per bag, 12 pairs per dozen, 72 pairs per case | | | | | | |
| CASE WEIGHT | 6 | 7 | 8 | 9 | 10 | 11 | |
| | 4 Kgs | 4.1 Kgs | 4.2 Kgs | 4.5 Kgs | 5 Kgs | 5.2 Kgs | |
| C00 | China | | | | | | |







DIMENSIONS (IN/CM)

| A | 8.6 / 22 | 9 / 23 | 9.4 / 24 | 9.8 / 25 | 10.2 / 26 | 10.6 / 27 |
|---|-----------|---------|-----------|----------|------------|------------|
| В | 3.3 / 8.5 | 3.5 / 9 | 3.7 / 9.5 | 4 / 10 | 4.1 / 10.6 | 4.3 / 10.8 |
| Н | Purple | Red | Yellow | ■ Brown | ■ Black | Blue |

PERFORMANCE PROPERTIES

| EN388: 3X42E | ASTM F2992-15 ANSI Cut Level A5 (Adopted by ANSI/ISEA 02/16) | | | | | | |
|-----------------|--|---|---|---|---|---|--|
| ABRASION | 0 | 1 | 2 | 3 | 4 | - | |
| CUT (2003) | Х | 1 | 2 | 3 | 4 | 5 | |
| TEAR | 0 | 1 | 2 | 3 | 4 | - | |
| PUNCTURE | 0 | 1 | 2 | 3 | 4 | - | |
| CUT (ISO 13997) | Α | В | С | D | Е | F | |

