

TECHNICAL SHEET

16-560E

G-TEK® POLYKOR™ SEAMLESS KNIT BLENDED GLOVE WITH POLYURETHANE COATED SMOOTH GRIP



- PolyKor™ shell is lightweight and provides excellent dexterity, tactile sensitivity and cut resistance
- Polyurethane coated palm and fingertips for great abrasion resistance, excellent puncture resistance and outstanding wet/dry grip
- Knit wrist helps prevent dirt and debris from entering the glove
- Economy and performance
- · Cotton color binding denotes sizing
- Washable, resistant to chemicals, water, and ultraviolet light

APPLICATIONS

- Electronics
- · Glass cutting
- · Sheet metal handling
- General duty
- Parts assembly
- · Sharp small parts handling

CARE INSTRUCTIONS

Recommend washing gloves in slightly warm water not exceeding 40°C. A mild non-ionic detergent should be used. A 5-10 minute cycle time should be employed. Tumble dry on low - maximum temperature 140°F (60°C).

TECHNICAL DATA

MATERIAL	PolyKor™ Fiber / Polyurethane					
CONSTRUCTION	Seamless knit					
COLOR	Shell: ■ Gray / Coating: ■ Gray					
WRIST STYLE	Knit wrist					
SIZES	6 -11					
PACKAGING	1 pair per bag, 12 pairs per dozen, 72 pairs per case					
CASE DIMENSIONS	14.2" x 11.8" x 12.6" / 36cm x 30cm x 32cm					
CASE WEIGHT	6	7	8	9	10	11
	8.4 lbs	8.8 lbs	9.7 lbs	10.1 lbs	10.6 lbs	11.9 lbs
	3.8 kgs	4 kgss	4.4 kgs	4.6 kgs	4.8 kgs	5.4 kgs
C00	China					

PERFORMANCE PROPERTIES

EN388: 4X42D	ASTM F2992-15 ANSI Cut Level A4 (Adopted by ANSI/ISEA 02/16)						
ABRASION	0	1	2	3	4	-	
CUT (2003)	Х	1	2	3	4	5	
TEAR	0	1	2	3	4	-	
PUNCTURE	0	1	2	3	4	-	
CUT(13997)	А	В	C	D	E	F	







DIMENSIONS (IN/CM)

A	8.6 / 22	8.9 / 22.5	9.3 / 23.5	9.6 / 24.5	10 / 25.5	10.6 / 27
В	3.5 / 9	3.7 / 9.5	3.8 / 9.8	3.9 / 10	4.1 / 10.5	4.3 / 11
Н	Purple	Red	Yellow	Brown	■ Black	Blue

