



TECHNICAL SHEET

41-1415

G-TEK® POLYKOR® HI-VIS SEAMLESS KNIT ACRYLIC LINED GLOVE WITH DOUBLE-DIPPED NITRILE COATED FOAM GRIP

- Seamless construction for a comfortable fit
- Acrylic gloves provide economical cold weather protection
- Nitrile foam coating provides superior grip in dry, wet and oily applications
- Fully coated flat nitrile helps keep hands dry in wet applications
- Knit wrist helps prevent dirt and debris from entering the glove
- Hi-vis coloring makes this product very easy to see
- Excellent thermal insulation
- Heat resistant up to 350 °C
- Quickly evaporates moisture from the skin
- Extra softness for non-chafing comfort
- Launderable for extended life and to reduce replacement costs
- Cotton color binding denotes sizing

APPLICATIONS

- Refrigerated areas
- Utilities
- Food processing
- Commercial fishing
- Construction
- Outdoor winter activities & recreation

CARE INSTRUCTIONS

Recommend washing gloves in slightly warm water not exceeding 104°F (40°C). A mild non-ionic detergent should be used. A 5-10 minute cycle time should be employed. Tumble dry on low, maximum temperature 140°F (60°C).

TECHNICAL DATA

| | | | | |
|-------------|---|---------|---------|---------|
| MATERIAL | Polyester (15 Gauge) / Acrylic (7 Gauge) / Nitrile Foam Coating | | | |
| CUFF STYLE | Knit wrist | | | |
| COLOR | Shell: ■ Yellow HV / Coating: ■ Black/Blue | | | |
| SIZES | 8-10 | | | |
| PACKAGING | Single polybag, pack of 12, case of 72 | | | |
| CASE | 40cm x 28cm x 50cm | | | |
| CASE WEIGHT | 8 | 9 | 10 | 11 |
| | 9.5 kg | 10.5 kg | 11.5 kg | 12.5 kg |
| COO | China | | | |


PERFORMANCE PROPERTIES

| | | | | | | |
|---------------------|--|---|---|---|---|---|
| EN388: 4X32C | ASTM F2992-15 ANSI Cut Level A4 (Adopted by ANSI/ISEA 02/16) | | | | | |
| ABRASION | 0 | 1 | 2 | 3 | 4 | - |
| CUT (2003) | X | 1 | 2 | 3 | 4 | 5 |
| TEAR | 0 | 1 | 2 | 3 | 4 | - |
| PUNCTURE | 0 | 1 | 2 | 3 | 4 | - |
| CUT (ISO 13997) | A | B | C | D | E | F |



DIMENSIONS (IN/CM)

| | 8 | 9 | 10 | 11 |
|----------|--|--|--|---|
| A | 10.6 / 27 | 11 / 28 | 11.4 / 29 | 11.8 / 30 |
| B | 4.5 / 11.5 | 4.7 / 12 | 4.9 / 12.5 | 5.1 / 13 |
| H | ■ Yellow | ■ Black | ■ Blue | ■ Bue |



PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®

PIP FRANCE SAS | 120 Grande Rue | 85570 L'Hermenault | Tel: +33 2 51 50 19 80 | info@pipeurope.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED.