






Scheda tecnica calzatura/Shoes technical data sheet


Identificazione articolo/Item identification				
Cod. comm.le Industrial Starter/ IS commercial item code:	46200	Cod. art. fornitore/ Supplier item code:	IS10 slip on	Cod. fornitore/ Supplier code: 101479
Cod. colore Industrial Starter/ Industrial Starter colour code:	-	<input checked="" type="checkbox"/>	Articolo del catalogo/Item from catalogue	
		<input type="checkbox"/>	Articolo personalizzato/Customized item	
		Codice cliente/Customer code:		N/A
Nome articolo/Item name:	"EXTREME STRETCH SLIP ON" S3 SRC ESD			

Descrizione tecnica dell'articolo/Technical item description			
Componente / Component	Materiale / material	Composizione / Composition	Spessore / Thickness
Puntale / Toe	Microfibra / Microfiber	50% nylon + 50% poliuretano / 50% nylon + 50% polyurethane	0.8 mm
Laterale / Vamp	Mesh - Stampa/ Mesh - Printing	100% terylene / 100% terylene	
Sottoocchiello / Eyestay	Stampa / Printing		
Quartiere / Quarter	Microfibra / Microfiber		
Collarino esterno + linguetta / Outside collar + tongue	Lycra + 1.5 mm SBR / Lycra + 1.5mm SBR		
Tallone / Heel	Microfibra / Microfiber	50% nylon + 50% poliuretano / 50% nylon + 50% polyurethane	1.4 mm
Gancio / Hook	Plastica / Plastic	Nylon / Nylon	
Fettuccia / Webbing	Tessuto / Webbing	Poliestere / Polyester	
Fodera / Lining	Mesh / Mesh	Terylene + PPG + tricot / Terylene + PPG + tricot	
Lacci / Laces	Poliestere / Polyester		
Fodera anteriore / Front Lining	Mesh / Mesh	100% terylene / 100% terylene	
Imbottitura collare / Collar padding	Schiuma / Foam	PPG / PPG	10 mm
Sottopiede copertura / Footbed cover	Mesh / Mesh	100% terylene / 100% terylene	
Sottopiede fondo posteriore / Footbed bottom back	Polietilene Alta Densità / Hi Poly	PPG / PPG	
Sottopiede fondo anteriore/ Footbed bottom front	Polietilene Alta Densità / Hi Poly	PPG / PPG	
Lamina antiperforazione / Lasting Board	4 mm Lasted Board / 4 mm Lasted Board	Terilene + Gomma / Terylene + Rubber	4 mm
Puntale / Toe Cap	Composito / Composite	Fibra di vetro + nylon / Fiber Glass + nylon	
Suola / Outsole	Poliuretano / Polyurethane	Poliuretano / Polyurethane	
Intersuola / Midsole	Poliuretano / Polyurethane	Poliuretano / Polyurethane	
Cambrione / Shank	Plastica / Plastic	Nylon / Nylon	

Scheda tecnica calzatura/Shoes technical data sheet



Loghi / Logos :	ISSALINE 
Taglie / Sizes:	36-48
Imballo / Packaging:	n. 1 prs / box – n. 5 boxes / export carton
Note / Notes:	<p>Shank System</p> <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  TEXTILE </div> <div style="text-align: center;">  FIBER GLASS </div> <div style="text-align: center;">  METAL FREE </div> <div style="text-align: center;">  ULTRA FLEX </div> </div>

Conformità alle norme CE/Conformity with EC standards

Cat. DPI / PPE Category:	II	Norme CE e livelli di protezione/ EC standards and protection levels:	EN ISO 20345: 2011 S1P SRC	
Certificato d'esame UE del tipo n° / UE type-examination certificate No.:	BP 50552949 0001		Data / Date:	12.08.2022
Organismo notificato/ Notified body:	TuV Rheinland		N°/ No.:	0197
Lingue nota informativa/ Information note's languages:	FR / RS / SK / HR / SI / IT / EN / ES / CZ / PL / PT			



Foto / Photo



Vicenza (Italy), 20/08/2022

Resp. acquisti/Purchasing manager